

# POWER MODULE 30KW



## FEATURES


- ◆ Up to 30kW Output Capacity.
- ◆ Designed to Optimise Energy Conversion Efficiency.
- ◆ Electrical Isolation Between High and Low Voltage Components.
- ◆ Prevent Short Circuits and Protect Against Overcurrent Conditions.
- ◆ Efficient Thermal Management.

## APPLICATIONS



Fast Charging Station | On-board Charger | Battery Charger

## OUTPUT GRAPH



## TECHNICAL SPECIFICATIONS

### AC Input

Voltage	380 VAC ± 10% (3P+N+PE)
Voltage Range	285 to 475 VAC
Frequency	50 to 65Hz
Power Factor	≥ 0.99
Total Harmonic Distortion (THD)	≤ 5%

### DC Output

Voltage Range	50 to 1000 VDC
Constant Power Range	250 to 500 VDC   500 to 1000 VDC <i>(High and Low Mode Auto Switching)</i>
Current Range	0.5 to 120 A
Power Output	30 kW
Voltage Regulation Accuracy	≤ ± 0.5%
Current Regulation Accuracy	≤ ± 1%
Current Sharing Imbalance	≤ ± 5%
Peak Efficiency	≥ 96%

### Interface

Communication Protocol	CAN
------------------------	-----

### Protection

Input Over Voltage Protection	490 VAC ± 10%
Input Under Voltage Protection	270 VAC ± 10%
Short Circuit Protection	Self-Roll Back Protection

### Environment

Operating Temperature	-30°C to 75°C (>55°C Output Derating)
Storage Temperature	-40°C to 75°C
Relative Humidity	5 to 95% No Condensation
Altitude	≤ 2000 m, Derating Above 2000 m
Cooling Method	Fan Cooling

### Mechanical

Address Setting	Digital Screen Display & Button Operation
Dimension (L x W x H)	437.5 X 336 X 84 mm
Weight	< 16 kg

### Other Operational Specs

Mean Time Between Failures (MTBF)	500000 hours
Standby Power Consumption	< 13 W

