

CCS2 EV SIMULATOR 120 KW



FEATURES

- ◆ Fully automatic EV simulation.
- ◆ Support three simulator modes: quick test, regular test, and charging test.
- ◆ An informative and easy-to-use HMI user interface.
- ◆ Generate the simulator test report via USB in CSV format.
- ◆ Rugged and portable carrying case ideal for outdoor testing.

APPLICATIONS



EVSE | EV | R&D

TECHNICAL SPECIFICATIONS

Input power

Supply Voltage	230 VAC \pm 10% (P+PE +N)
Input Frequency	50Hz

Voltage Measurement

Range	0 to 1000 V DC
-------	----------------

Current Measurement

Range	0 to 200 A
-------	------------

Connector

Type	IEC 60309 Industrial Socket (CCS2 DC-1)
------	---

Communication

Protocol Standards	ISO 15118 & DIN 70121
--------------------	-----------------------

Interface

HMI Display	7" TFT Resistive Type Touch Display
-------------	-------------------------------------

Mechanical

Degree of Protection	Closed Lid: IP66; Open Lid: IP43
Operating Temperature	0°C to 70°C
Storage Temperature	0°C to 70°C
Humidity	5% to 95%
Dimension (LxBxH)	610 × 440 × 326 mm



+91-9016028817



systems@bacancy.com



bacancysystems.com